

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005UK		wheelbase 1795+2980+1400 mm
006CI		rear frame overhang 800 mm
018SI		engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAE		instrument panel km/h 'High-Line'
022GE		gearbox ZF 16 S 252 OD
023EH		fuel tank 400l right
025ML		front axle VO-09/VO-09 straight
026EF		front springs parabolic 9,5 t
027AP		radiator and intercooler for over 35 degrees ambient temperature
028FP		rear springs parabolic 16 t
028PA		Anbau Doppelachse
029GC		propshafts for increased load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035LF		planetary axle ratio i = 4.33
037AC		with differential lock in rear axle
038GH		disc wheels 10 hole 11.75-22.5 on 1st FA TL
038JH		disc wheels 10-hole 11.75-22.5 on 2nd front axle TL
038PG		disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TH		disc wheel 10-hole 11.75-22.5 as spare wheel TL
042CY		EC tachograph electronic, automatic, 2 drivers (no EU-approval since 2006)
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide, 1880mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment
080AE		door interior panelling washable
116AE		visco fan
116AZ		fan control for countries with high temperature
118EK		short mounting base (only engine)
118MA		EDC engine regulation
119EH		general parameterisation for power take-offs
122QN		PTO NH/4C without flange f=1.17/1.40 right horizontal
123AC		guard plate for 1 tank
123CC		strainer for fuel tank
124AL		fuel filter
124AZ		additional fuel filter with water trap
133MA		actuating system for tipper body
153KC		air conditioning system AC R134A with automatic temperature control without CFHC

159XS		without cab insulation NORDIC (against cold) for M, L and LX cab
194AC		operator's manual in French
194EA		additional operator's manual in ENGLISH
201AR		air intake upswept with dry air filter / precleaner
201EM		air filter element with safety element for heavy-duty operation
201FA		fine dust and pollen filter
203EK		connection for external engine speed control (ZDR)
205AN		air compressor 1-cylinder, 360 ccm
206EY		exhaust on rh side with tail pipe to rear
208AK		exhaust valve brake
210XX		without flame starting system/ additional starting aid device
211FF		single-plate clutch MFZ 430
227AC		rear axle breather upswept
230AH		rear underride guard, round
230XW		without front underride guard
230YX		without lateral underride guard
233EM		3-part steel bumper
234EA		towing coupling RINGFEDER 6451
236AF		cross member for trailer coupling
241AH		body attachment brackets bolted
245XX		without spare wheel holder
256AA		steering wheel lock
256EA		emergency steering pump
258HA		anti-lock braking system (ABS)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262XX		without brake connection on frame end
272FA		entry lighting for driver and co-driver
276AC		armrests for driver's seat
280EU		stoneguard grille in front of radiator
281AB		medium-height design
283FB		cab mounts on coil springs for 'M' cab
303AM		tank cap lockable - 1 cap with vent (not licensable according to ECE-R34)
310EE		halogen twin headlights H7 for right-hand traffic
311AA		protective grille for headlights headlights
311AE		protective grille for taillamps
318AA		marker lamps
318AK		side marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EE		language 1 'French' for display in instrument panel
325FC		language 2 'English' for display in instrument panel
326XY		without 12/24 V socket at frame end
327AF		battery main switch, mechanical
329CS		batteries 12V 155Ah, 2 pcs
329ER		battery box up to 175Ah
329HC		service note for batteries "maintenance-free"
331AB		alternator Basic
339FP		Display on the dashboard for operating data
343AN		acoustic warning system for engaged reverse gear at frame end
345AU		Speed limiter, electronic 89 km/h + 1 km/h tolerance
345EA		cruise control
346CA		charging pressure indicator
350NL		radio MAN BasicLine 24V
350XO		without navigation SD
352ED		preparation for additional lighting on cab roof
352FD		preparation for installation of flashing lights

176XH		without mattress for lower bunk
176XK		without mattress for upper bunk
176XL		No bunks for 'M', 'C', 'DK' cabs
180AC		windscreen of laminated glass tinted
180CA		door windows tinted
181AA		cab rear wall without windows
181XC		without curtain before bunks
181YX		without all-round curtain
184CD		safety belt display, driver's side
185AT		side windows tinted behind B-post
186AS		mechanical sliding roof
187AF		electric door window lifters for driver and co-driver
188AH		roller blind for windscreen, mechanical
188AK		sun shade in front of windscreen
189AC		handles left and right (on B-post)
189AD		handles left and right (on A-post)
190XN		without waste paper bins between theseats
190XX		without oddment box
192AH		kerb mirror, right
192CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
192HA		mirror arms for body width 2500-2600 mm width 2500 mm
192XJ		Without front mirror on co-driver's side/in the middle
100AH		mudflap front
101AS		mudguard cover for transfer
101CQ		Plastic mudguard, rear (half shell; without rain spray inhibitor)
101EL		3-part synthetic mudguards for 2nd front axle
104AP		spray reducer
105AC		first-aid kit
105AK		hazard-warning sign
105AR		hazard-warning lamp
105CP		20 m tyre inflator hose with pressure gauge
107AA		jack 25 t
111AA		1 chock
134CH		smoker-package
123AE		signs in French
123AM		signs additionally in Arabic
138AE		plastic floor and engine tunnel covering
142FC		anti-noise package 80 dB (92/97EEC)
100AC		Fittings for right-hand traffic
198LF		Height across cab unloaded up to 4000 mm
.QW01		chassis in water-based paint
.VS01		chassis graphite black RAL 9011 matt
.VS02		wheels White aluminium acrylic RAL 9006
.VS03		cab Pure white RAL 9010
10001		2 wahlweise 385/65R22,5 LENK-S+G TL
10002		2 wahlweise 385/65R22,5 LENK-S+G TL
10001		4 wahlweise 315/80R22,5 ANTR-S+G TL
10002		4 wahlweise 315/80R22,5 ANTR-S+G TL
10004		1 wahlweise 385/65R22,5 LENK-S+G TL